

**IN THE CLAIMS:**

This listing of claims provided below will replace all prior versions and listings of claims in the application.

1. (Previously Presented) An ink set for inkjet recording for forming a black image portion in a color image with a black ink and a color ink, wherein the black ink comprises cationic or anionic self-dispersible carbon black and the color ink comprises self-dispersible pigment having an opposite polarity to that of the self-dispersible carbon black.

2. (Previously Presented) The ink set for inkjet recording of claim 1, wherein the self-dispersible carbon black is cationic and the color ink comprises at least an anionic self-dispersible pigment.

3. (Currently Amended) The ink set for inkjet recording of claim 1, wherein the carbon black is contained in an amount of 0.1 to ~~10~~ 20 % by mass relative to a total amount of the ink containing the black ink.

4. (Previously Presented) The ink set for inkjet recording of claim 1, wherein the black ink and/or color ink contain a surfactant.

5. (Previously Presented) The ink set for inkjet recording of claim 1, wherein the black ink comprises a compound represented by formula (1):



wherein R is a functional group having 4 to 8 carbon atoms selected from the group consisting of an alkyl group, an alkenyl group, an alkynyl group, a phenyl group, an alkylphenyl group, an alkenylphenyl group and a cycloalkyl group; X is an oxyethylene group or an oxypropylene group; and n is an integer from 1 to 4.

6. (Previously Presented) A method for inkjet recording comprising:  
recording a color image in accordance with recording signals by ejecting from an orifice a black ink and a color ink, wherein the black ink comprises cationic or anionic self-dispersible carbon black and

the color ink comprises a substance having an opposite polarity to that of the self-dispersible carbon black, and wherein a black image portion in the color image is formed with the black ink and the color ink, and a time lag between ejecting of the black ink and ejecting of the color ink is 20 ms or less.

7. (Previously Presented) The method for inkjet recording of claim 6, wherein the self-dispersible carbon black is cationic and the color ink comprises at least an anionic substance.

8. (Previously Presented) The method for inkjet recording of claim 6, wherein the order of ejecting the black ink and ejecting the color ink changes.

9. (Original) The method for inkjet recording of claim 6, wherein the carbon black is contained in an amount of 0.1 to 20 % by mass relative to a total amount of the ink containing the black ink.

10. (Previously Presented) The method for inkjet recording of claim 6, wherein the black ink and/or the color ink contain a surfactant.

11. (Previously Presented) The method for inkjet recording of claim 6, wherein the black ink comprises a compound represented by formula (1):



wherein R is a functional group having 4 to 8 carbon atoms selected from the group consisting of an alkyl group, an alkenyl group, an alkynyl group, a phenyl group, an alkylphenyl group, an alkenylphenyl group and a cycloalkyl group; X is an oxyethylene group or an oxypropylene group; and n is an integer from 1 to 4.

12. (Previously Presented) An apparatus for inkjet recording for forming a color image comprising:

an ink cartridge for ejecting a black ink and another ink cartridge for ejecting a color ink, wherein the black ink comprises cationic or anionic self-dispersible carbon black and the color ink comprises a substance having an opposite polarity to that of the self-dispersible carbon black, and wherein a black image portion in the color image is formed with the black ink and the color ink, and a time lag between

ejecting of the black ink and ejecting of the color ink is 20 ms or less.


13. (Previously Presented) The apparatus for inkjet recording of claim 12, wherein the self-dispersible carbon black is cationic and the color ink comprises at least an anionic substance.

14. (Previously Presented) The apparatus for inkjet recording of claim 12, wherein recording is carried out by reciprocal scanning of the ink cartridge for ejecting a black ink and the another ink cartridge for ejecting a color ink, and the order of ejecting the black ink and ejecting the color ink changes by the reciprocal scanning.

15. (Previously Presented) The apparatus for inkjet recording of claim 12, wherein the carbon black is contained in an amount of 0.1 to 20% by mass relative to a total amount of the ink containing the black ink.

16. (Previously Presented) The apparatus for inkjet recording of claim 12, wherein the black ink and/or the color ink contain a surfactant.

17. (Previously Presented) The apparatus for inkjet recording of claim 12, wherein the black ink comprises a compound represented by formula (1):



wherein R is a functional group having 4 to 8 carbon atoms selected from the group consisting of an alkyl group, an alkenyl group, an alkynyl group, a phenyl group, an alkylphenyl group, an alkenylphenyl group and a cycloalkyl group; X is an oxyethylene group or an oxypropylene group; and n is an integer from 1 to 4.

18. (Previously Presented) The method of claims 4, 10, or 16, wherein the surfactant is present in an amount of from about 0.001 to 5 % by mass relative to the amount of the black ink and the amount of the color ink, respectively.